

# MIC 600~3300TL-X

- Maximum efficiency of 97.6%
- Compact design
- Touch key& OLED display
- Flexible monitoring options
- AFCI optional



P O W E R  
- I N G O  
T O M O -  
R R O W O



[www.ginverter.com](http://www.ginverter.com)

Datasheet	MIC 600TL-X	MIC 750TL-X	MIC 1000TL-X	MIC 1500TL-X	MIC 2000TL-X	MIC 2500TL-X	MIC 3000TL-X	MIC 3300TL-X
<b>Input data (DC)</b>								
Max. recommended PV power (for module STC)	1050W	1050W	1400W	2100W	2800W	3500W	4200W	4290W
Max. DC voltage	500V	500V	500V	500V	500V	550V	550V	550V
Start voltage	50V	50V	50V	50V	50V	80V	80V	80V
Nominal voltage	120V	120V	180V	250V	360V	360V	360V	360V
MPP voltage range	50V-500V	50V-500V	50V-500V	50V-500V	50V-500V	65V-550V	65V-550V	65V-550V
No. of MPP trackers	1							
No. of PV strings per MPP tracker	1							
Max. input current per MPP tracker	13A							
Max. short-circuit current per MPP tracker	16A							
<b>Output data (AC)</b>								
AC nominal power	600W	750W	1000W	1500W	2000W	2500W	3000W	3300W
Max. AC apparent power	600VA	750VA	1000VA	1500VA	2000VA	2500VA	3000VA	3300VA
Nominal AC voltage(range*)	230V (180-280V)							
AC grid frequency(range*)	50/60 Hz (45-55Hz/55-65 Hz)							
Max. output current	2.9A	3.6A	4.8A	7.1A	9.5A	11.9A	14.3A	14.3A
Adjustable power factor	0.8leading...0.8lagging							
THDi	<3%							
AC grid connection type	Single phase							
<b>Efficiency</b>								
Max. efficiency	96.5%	97.4%	97.4%	97.4%	97.4%	97.6%	97.6%	97.6%
European efficiency	95.5%	96.5%	96.5%	97.0%	97.0%	97.0%	97.1%	97.1%
MPPT efficiency	99.9%							
<b>Protection devices</b>								
DC reverse polarity protection	Yes							
DC switch	Yes							
AC/DC surge protection	Type III / Type III							
Insulation resistance monitoring	Yes							
AC short-circuit protection	Yes							
Ground fault monitoring	Yes							
Grid monitoring	Yes							
Anti-islanding protection	Yes							
Residual-current monitoring unit	Yes							
AFCI protection	Optional							
<b>General data</b>								
Dimensions (W / H / D)	274/254/138mm							
Weight	6kg	6kg	6kg	6kg	6kg	6.2kg	6.2kg	6.2kg
Operating temperature range	-25°C ... +60°C							
Nighttime power consumption	< 0.5W							
Topology	Transformerless							
Cooling	Natural convection							
Protection degree	IP65							
Relative humidity	0-100%							
Altitude	4000m							
DC connection	H4/MC4(Optional)							
AC connection	Connector							
Display	OLED+LED/WIFI+APP							
Interfaces: RS485 / USB/WI-FI/ GPRS/ RF/LAN	Yes/Yes/Optional/Optional/Optional /Optional							
Warranty: 5 years / 10 years	Yes /Optional							
CE,AS4777, AS/NZS 3100, CEI 0-21, VDE-AR-N 4105, VDE 0126-1-1, UTE C 15-712-1, EN50549, IEC 60068, IEC 61683, IEC 62116, IEC 61727, INMETRO, G98, C10/C11, UNE217001, UNE206007, PO12.2								

\* The AC voltage and frequency range may vary depending on specific country grid standard.  
All specifications are subject to change without notice.